




Type

- 4 Stroke
- Air Cooled
- V Twin
- Overhead valve
- Vertical Shaft

Performance curves

The power rating of this engine is the Net power rating tested on a production engine and measured in accordance with SAE J1349. Actual power output will vary depending on numerous factors, including, but not limited to, the operating speed of the engine in application, environmental conditions, maintenance, and other variables.



Technical Specifications

▪ Engine Type	4-Stroke, Vertical Shaft, V-Twin, OHV, Air-cooled,
▪ Max. power	16.6 kW (22.2 hp) / 3600 rpm
▪ Oil capacity	2.2 litres
▪ Number of cylinders	2
▪ Displacement	726cm ³
▪ Dimensions (L x W x H) (mm)	479 x 462 x 565
▪ Bore x stroke	78 x 76 mm
▪ Fuel tank capacity	
▪ Max. torque	54.3 Nm (40.0 ft.lbs) / 2000 rpm
▪ Dry weight	46.0 Kg

Features

- High performance lubrication system
- Cast iron cylinder liners
- Internally vented carburetor with fuel shut-off solenoid
- Automatic compression release
- Dual stage canister air filter
- Metal engine cover
- 90 degree V-twin
- Electronic spark ignition
- Spherical combustion chambers
- Clean out ports
- Heavy duty shift type starter
- Overhead V-valves
- Rotating grass screen

Options

- Shaft variations
- Various speed control system
- 20 Amp charge coil
- Various oil drains
- Oil pressure switches
- Muffler

